



Agentic Concolic Execution

Zhengxiong Luo, Huan Zhao, Dylan Wolff, Cristian Cadar, Abhik Roychoudhury


{luozx, abhik}@nus.edu.sg, {zhaohuan, wolffd}@comp.nus.edu.sg, c.cadar@imperial.ac.uk




Imperial College
London

Dynamic Symbolic Execution (DSE)


- Widely-used for program analysis / vuln. detection
- Use ***symbolic values*** as program inputs to systematically explore possible program behaviors




Applying DSE on Modern Software




Applying DSE on Modern Software



Applying DSE on Modern Software



Applying DSE on Modern Software



A Motivating Example

```
1  // assume start < end
2  int count(float start, float end) {
3      int iter_count = 0;    // final answer
4      for (float cur = start; cur != end; iter_count++) {
5          unsigned temp;
6          memcpy(&temp, &cur, sizeof(float));
7          temp++;
8          memcpy(&cur, &temp, sizeof(float));
9      }
10
11     if (iter_count <= 20)
12         printf("BUG triggered!");
13 }
```

A Motivating Example



```
1 // assume start < end
2 int count(float start, float end) {
3     int iter_count = 0; // final answer
4     for (float cur = start; cur != end; iter_count++) {
5         unsigned temp;
6         memcpy(&temp, &cur, sizeof(float)); temp <- cur
7         temp++; temp <- temp + 1
8         memcpy(&cur, &temp, sizeof(float)); cur <- temp
9     }
10
11     if (iter_count <= 20)
12         printf("BUG triggered!");
13 }
```



Count # of **representable**
floating point values in
[start, end)

Challenge-1: Symbolic Modeling

```
1 // assume start < end
2 int count(float start, float end) {
3     int iter_count = 0;    // final answer
4     for (float cur = start; cur != end; iter_count++) {
5         unsigned temp;
6         memcpy(&temp, &cur, sizeof(float));
7         temp++;
8         memcpy(&cur, &temp, sizeof(float));
9     }
10
11     if (iter_count <= 20)
12         printf("BUG triggered!");
13 }
```



Complex and incomplete symbolic modelling

Huge manual effort to support each *language & code construct & env*

Challenge-2: Constraint Solving

```
1 // assume start < end
2 int count(float start, float end) {
3     int iter_count = 0;    // final answer
4     for (float cur = start; cur != end; iter_count++) {
5         unsigned temp;
6         memcpy(&temp, &cur, sizeof(float));
7         temp++;
8         memcpy(&cur, &temp, sizeof(float));
9     }
10
11     if (iter_count <= 20)
12         printf("BUG triggered!");
13 }
```

f

Symbolic Store σ

start $\mapsto \alpha$
end $\mapsto \beta$
iter_count $\mapsto i$


Initial Input

start = 1.0
end = 1.00001
(84 for-loop iterations)

Path Constraints

> 1000 clauses

$$\bigwedge_{i=0}^{n-1} (f^i(\alpha) \neq \beta) \wedge (f^n(\alpha) = \beta) \wedge (n > 20)$$



Verbose, mechanical constraint representation

Solvers struggle with large constraints or hard theories (e.g. string, floating-point, ...)

LLM is Here to Rescue...

Symbolic Modeling

Possess vast knowledge *across*



Programming
Languages



Code
Constructs



Program
Environment

Constraint Solving

$$\bigwedge_{i=0}^{n-1} (f^i(\alpha) \neq \beta) \wedge (f^n(\alpha) = \beta) \wedge (n > 20)$$

*find 2 FP numbers w/ ≤ 20
representable numbers in between*



Solve



e^x

LLM is Here to Rescue...

Symbolic Modeling

Possess vast knowledge *across*



Programming
Languages



Code
Constructs



Program
Environment

Constraint Solving

$$\bigwedge_{i=0}^{n-1} (f^i(\alpha) \neq \beta) \wedge (f^n(\alpha) = \beta) \wedge (n > 20)$$

*find 2 FP numbers w/ ≤ 20
representable numbers in between*



Solve




e^x


Risk: LLMs are slow, untrustworthy, and can hallucinate

Our work: ConcoLLMic =
LM
Agentic Concolic Execution

Our work: ConcoLLMic



ConcoLLMic: Overview



ConcoLLMic: Execution Tracking

- *Source-code* level instrumentation – LLMs’ multilingual capability

enter [func_name] [BB_ID] →

Original Code Block {

exit [func_name] [BB_ID] →

```
int main(int argc , char **argv) {  
    fprintf(stderr, "enter main 1");  
    float start = atof(argv [1]), end = atof(argv [2]);  
    count(start , end);  
    fprintf(stderr, "exit main 1");  
}
```

- *Unified* abstraction of execution traces

Global context information →

Executed code {

Untaken branch condition
with coverage info →

```
// Omitted Imports, Definitions & Variable Declarations  
1 // assume start < end  
2 int count(float start, float end) {  
3     int iteration_count = 0;    // final answer  
4     for (float cur = start; cur != end; iteration_count++) {  
5         unsigned temp;  
6         memcpy(&temp, &cur, sizeof(float));  
7         temp++;  
8         memcpy(&cur, &temp, sizeof(float));  
9     }  
10  
11     if (iteration_count <= 20)  
12         // Unexecuted line 12 removed. Line cov: 0/1  
13 }
```

ConcoLLMic: Summarization Agent (1/4)

Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

Execution Abstraction

- ①  Func Call Chain [src/main.c] main => [src/count.c] count
- ②  Executed Lines count.c (13 lines total)

```
// Omitted Imports, Definitions & Variable Declarations
1 // assume start < end
2 int count(float start, float end) {
3     int iteration_count = 0;    // final answer
4     for (float cur = start; cur != end; iteration_count++) {
5         unsigned temp;
6         memcpy(&temp, &cur, sizeof(float));
7         temp++;
8         memcpy(&cur, &temp, sizeof(float));
9     }
10
11     if (iteration_count <= 20)
12         // Unexecuted line 12 removed. Line cov: 0/1
13 }
```



Given : ① harness ② execution abstraction...

Task : select target branch & generate path constraints

Tools : <CODEREQUEST, THINK, CHOOSEBRANCH, SUMMARIZE>



ConcoLLMic: Summarization Agent (2/4)

Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

Execution Abstraction

- ①  Func Call Chain [src/main.c] main => [src/count.c] count
- ②  Executed Lines count.c (13 lines total)
- ```
// Omitted Imports, Definitions & Variable Declarations
1 // assume start < end
2 int count(float start, float end) {
3 int iteration_count = 0; // final answer
4 for (float cur = start; cur != end; iteration_count++) {
5 unsigned temp;
6 memcpy(&temp, &cur, sizeof(float));
7 temp++;
8 memcpy(&cur, &temp, sizeof(float));
9 }
10
11 if (iteration_count <= 20)
12 // Unexecuted line 12 removed. Line cov: 0/1
13 }
```
- 

**Given :** ① harness ② execution abstraction...

**Task :** select target branch & generate path constraints

**Tools :** <CODEREQUEST, THINK, CHOOSEBRANCH, SUMMARIZE>



{CODEREQUEST} count.c, line 12



|12|Uncovered|: printf("BUG triggered!");



# ConcoLLMic: Summarization Agent (3/4)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Execution Abstraction

①  Func Call Chain [src/main.c] main => [src/count.c] count

②  Executed Lines count.c (13 lines total)

```
// Omitted Imports, Definitions & Variable Declarations
1 // assume start < end
2 int count(float start, float end) {
3 int iteration_count = 0; // final answer
4 for (float cur = start; cur != end; iteration_count++) {
5 unsigned temp;
6 memcpy(&temp, &cur, sizeof(float));
7 temp++;
8 memcpy(&cur, &temp, sizeof(float));
9 }
10
11 if (iteration_count <= 20)
12 // Unexecuted line 12 removed. Line cov: 0/1
13 }
```



Given : ① harness ② execution abstraction...

Task : select target branch & generate path constraints

Tools : <CODEREQUEST, THINK, CHOOSEBRANCH, SUMMARIZE>



{CODEREQUEST} count.c, line 12



|12|Uncovered|: printf("BUG triggered!");



{CHOOSEBRANCH}

[target\_branch] if (iteration\_count <= 20) => True

[rationale] It represents a key behavior & has 0% cov.

[lines\_to\_cover] count.c:12-12



Your selection is recorded!



# ConcoLLMic: Summarization Agent (4/4)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Execution Abstraction

①  Func Call Chain [src/main.c] main => [src/count.c] count

②  Executed Lines count.c (13 lines total)

```
// Omitted Imports, Definitions & Variable Declarations
1 // assume start < end
2 int count(float start, float end) {
3 int iteration_count = 0; // final answer
4 for (float cur = start; cur != end; iteration_count++) {
5 unsigned temp;
6 memcpy(&temp, &cur, sizeof(float));
7 temp++;
8 memcpy(&cur, &temp, sizeof(float));
9 }
10
11 if (iteration_count <= 20)
12 // Unexecuted line 12 removed. Line cov: 0/1
13 }
```



Given : ① harness ② execution abstraction...

Task : select target branch & generate path constraints

Tools : <CODEREQUEST, THINK, CHOOSEBRANCH, SUMMARIZE>



{CODEREQUEST} count.c, line 12



|12|Uncovered|: printf("BUG triggered!");



{CHOOSEBRANCH}

[target\_branch] if (iteration\_count <= 20) => True

[rationale] It represents a key behavior & has 0% cov.

[lines\_to\_cover] count.c:12-12



Your selection is recorded!



{SUMMARIZE} [path\_constraint]

a) 2 CLI arguments: start < end

b) start, end are valid floating-points

c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$



# ConcoLLMic: Solving Agent (1/5)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Path Constraint (for target branch)

- a) 2 CLI arguments: start < end
- b) start, end are valid floating-points
- c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$

**Given :** ① harness ② new path constraints ...

**Task :** solve path constraint for a new input...

**Tools :** <EXECUTE\_CODE, QUERY\_SMT, THINK, GENERATE\_TEST>



# ConcoLLMic: Solving Agent (2/5)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Path Constraint (for target branch)

- a) 2 CLI arguments: start < end
- b) start, end are valid floating-points
- c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$


**Given :** ① harness ② new path constraints ...

**Task :** solve path constraint for a new input...


**Tools :** <EXECUTE\_CODE, QUERY\_SMT, THINK, GENERATE\_TEST>



{THINK} Original range  $[1.0, 1.00001)$  contains  $> 20$  representable floats.  
Let's fix start=1.0 and calculate end



{THINK} For float around 1.0, the smallest increment is  $\sim 2^{-23} \approx 1.19e^{-7}$   
So the range is  $\sim 20 \times 1.19e^{-7} \approx 2.38e^{-6}$  ... Let me try to verify ...



Your reasoning is recorded!



# ConcoLLMic: Solving Agent (3/5)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Path Constraint (for target branch)

- a) 2 CLI arguments: start < end
- b) start, end are valid floating-points
- c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$

**Given :** ① *harness* ② *new path constraints* ...

**Task :** solve path constraint for a new input...

**Tools :** <EXECUTE\_CODE, QUERY\_SMT, THINK, GENERATE\_TEST>



{THINK} Original range [1.0, 1.00001) contains > 20 representable floats.  
Let's fix start=1.0 and calculate end



{THINK} For float around 1.0, the smallest increment is  $\sim 2^{-23} \approx 1.19e^{-7}$   
So the range is  $\sim 20 \times 1.19e^{-7} \approx 2.38e^{-6}$ ... Let me try to verify ...




Your reasoning is recorded!



{EXECUTE\_CODE}

```
def next_float(f): ... # calculate next float

current = 1.0
for i in range(19):
 current = next_float(current)
print(next_float(current)); # the 20th value
```



Exec. Result: stdout = 1.000002384185791



# ConcoLLMic: Solving Agent (4/5)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Path Constraint (for target branch)

- a) 2 CLI arguments: start < end
- b) start, end are valid floating-points
- c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$

**Given :** ① harness ② new path constraints ...

**Task :** solve path constraint for a new input...

**Tools :** <EXECUTE\_CODE, QUERY\_SMT, THINK, GENERATE\_TEST>



{THINK} Original range [1.0, 1.00001) contains > 20 representable floats.  
Let's fix start=1.0 and calculate end



{THINK} For float around 1.0, the smallest increment is  $\sim 2^{-23} \approx 1.19e^{-7}$   
So the range is  $\sim 20 \times 1.19e^{-7} \approx 2.38e^{-6}$ ... Let me try to verify ...



Your reasoning is recorded!



{EXECUTE\_CODE}

```
def next_float(f): ... # calculate next float

current = 1.0
for i in range(19):
 current = next_float(current)
print(next_float(current)); # the 20th value
```




Exec. Result: stdout = 1.000002384185791



{GENERATE\_TEST} [is\_satisfiable] ✓

```
subprocess.run(["./count", "1.0", "1.000002384185791"])
```



# ConcoLLMic: Solving Agent (5/5)

## Harness

```
subprocess.run(["./count", "1.0", "1.0001"])
```

## Path Constraint (for target branch)

- a) 2 CLI arguments: start < end
- b) start, end are valid floating-points
- c) # IEEE-754 floating-point  $\in [\text{start}, \text{end}) \leq 20$

from summarization agent

## {CHOOSEBRANCH}

```
[target_branch] if (iteration_count <= 20) => True
[rationale] ...
[lines_to_cover] count.c:12-12
```

**Execution + Reachability Validation**

**Given :** ① harness ② new path constraints ...

**Task :** solve path constraint for a new input...

**Tools :** <EXECUTE\_CODE, QUERY\_SMT, THINK, GENERATE\_TEST>



{THINK} Original range [1.0, 1.00001) contains > 20 representable floats.  
Let's fix start=1.0 and calculate end



{THINK} For float around 1.0, the smallest increment is  $\sim 2^{-23} \approx 1.19e^{-7}$   
So the range is  $\sim 20 \times 1.19e^{-7} \approx 2.38e^{-6}$ ... Let me try to verify ...



Your reasoning is recorded!



## {EXECUTE\_CODE}

```
def next_float(f): ... # calculate next float

current = 1.0
for i in range(19):
 current = next_float(current)
print(next_float(current)); # the 20th value
```




Exec. Result: stdout = 1.000002384185791



{GENERATE\_TEST} [is\_satisfiable] ✓

```
subprocess.run(["./count", "1.0", "1.000002384185791"])
```




# Evaluation: Setup

LLM: *claude-sonnet-3.7* (200K context window)

Benchmark:  $8 \times$  Monolingual  $4 \times$  Polyglot

\* Max: 83 KLoC



Baselines: State-of-the-Art DSEs & Fuzzer



SymCC

SymSan



& Two variants

- Pending
- Float

# Evaluation: Coverage – Monolingual (C/C++)


KLEE  
+233%

KLEE-Pending  
+135%

SymCC  
+130%

SymSan  
+115%


AFL++  
+81%




# Evaluation: Coverage – Polyglot

Tested with *zero* additional setup effort. Consistent coverage growth.


 **ultrajson**




 **jansi**



 **py4j**




 **protobuf**




## Languages

-  Python
-  C
-  Java
-  C++
-  Go

# Evaluation: Coverage – Floating-Point Benchmark




# Evaluation: Bug Detection




# Findings 1: Slower Pace, Superior Results

- ✓ ConcoLLMic prioritizes input quality over quantity



# Findings 2: Reasoning Beyond Formal Solvers

- ✓ LLM agents reason about code path *without* relying on SMT






# Going Forward...

- ❖ Integration into conventional fuzzing


→ “*Agentic Orchestration for Hybrid Fuzzing*”, to appear  **NDSS**  
SYMPOSIUM/2027

- ❖ Location/Property-directed agentic concolic execution
- ❖ Agentic testing with stronger guarantees (e.g. proofs)
- ❖ Agentic testing of heterogeneous software (e.g. polyglot)

# Summary



**Risk:** LLMs are slow, untrustworthy, and can hallucinate



Paper



Code

